

TECHNICAL DATA SHEET (TDS)

UNIC GLOSS

Surface Enhancer & Sealer

1. PRODUCT DESCRIPTION

UNIC GLOSS is a ready-to-use, solvent-based satin-finish sealer formulated with high-quality acrylic resins for natural and artificial stones. It enhances the natural colour and provides a rich wet-to-glossy appearance while offering resistance to water, oil and stains.

2. ADVANTAGES

- Enhances natural stone colour
- Rich wet-look finish
- Non-yellowing formulation
- Easy penetration
- Stain resistance
- Water and oil repellency
- Maintains stone breathability
- Suitable for indoor and outdoor use
-

3. APPLICATION AREAS

Suitable for granite, silicate-based stones, lime-based stones and other suitable dark-coloured natural and artificial stones.

4. COVERAGE

Approximately 15–35 m²/L, depending on substrate porosity, texture and absorption. A test patch is recommended before application.

5. STORAGE & SHELF LIFE

Shelf life is approximately 12 months when stored in the original sealed container in a cool, dry place.

6. SURFACE PREPARATION

Ensure the surface is clean, dry and free from dust, dirt, oil and loose particles. Remove wax, epoxy and other existing coatings before application. Wash the surface to remove salts and contaminants that may affect penetration. Protect adjacent surfaces from accidental contact.

7. APPLICATION

Perform a small patch test to check appearance and compatibility. Apply UNIC GLOSS evenly using a saturated brush, roller or mop. Allow approximately 10–60 minutes drying time depending on site conditions. Highly absorbent surfaces may require an additional coat.

Ensure adequate ventilation during application. Allow 48–72 hours for complete curing and protect the treated surface from direct sunlight and water during the curing period.

8. TECHNICAL INFORMATION

Property	Specification
Appearance	: Mostly clear liquid
Odour	: Mild
Density	: 0.85 ± 0.1 g/cm ³

9. CAUTION

Use suitable personal protective equipment during application. Ensure proper ventilation. UNIC GLOSS does not protect stone against strong acids. Extremely worn or damaged surfaces should be restored or resurfaced before application. Always perform a patch test before full application.

Manufactured For & Marketed By:

UNICSTONE

Shop No.3, Ground Floor, Ashrama Road,
R T Nagar Post, Cholanagar, Situated at 1st Cross,
Bengaluru, Bengaluru Urban, Karnataka

E.: info.unicstone@gmail.com

M.: +91 78920 99925

ISO CERTIFIED COMPANY

